# zencontrol

### Six button sceneset datasheet



### **Features**

- 15 mA DALI line current
- Multiple finishes available
- Up to 10 units per DALI line
- Models to suit 64 and 80 mm mounting centres
- Selectable button additions on DALI-2 application controller



### Powered by DALI

No additional supply means energy savings and simple installation



#### DALI-2

For use with DALI-2 compliant application controller



## Integrated illumination

Configurable inbuilt LED status indicator for user convenience



### Customizavle

Customisable labels available for specific applications

## zencontrol

### Six button sceneset datasheet



### Product range

Order code	Description	
zc-sceneset-b6-blk	Six button, standard sceneset switch to suit 6 mm wall mount C-clip compatible, black finish	
zc-sceneset-b6-gr	Six button, standard sceneset switch to suit 60 mm wall mount, C-clip compatible, grey finish	
zc-sceneset-a6-blk	Six button, sceneset switch to suit 60 mm wall mount, black finish	
zc-sceneset-a6-gr	Six button, sceneset switch to suit 60 mm wall mount, grey finish	
zc-sceneset-a6-chp	Six button, sceneset switch to suit 86 mm wall mount, champagne finish	
zc-sceneset-a6-rgld	Six button, sceneset switch to suit 86 mm wall mount,rose gold finish	

#### **Features**

- 15 mA DALI line current
- Multiple finishes available
- Up to 10 units per DALI line
- Multiple control devices per line
- Designed for compliance to IEC 62386-301
- Customisable labels available for specific projects
- For use with DALI-2 compliant application controller
- Control scenes / groups / actions / events with a zencontrol control system

### **Notice**

- The switch must not be connected to any mains.
  It is powered directly from the DALI line.
- The DALI line is not SELV. It must be treated like LV mains and treated with the same precautions and wiring regulations.

### **Specifications**

DALI	
DALI-2	
15 mA	
0.5 - 0.75 mm <sup>2</sup> Strip 6 - 7 mm	
0 to 45°C	
PC UV stabilised, ABS, 316 stainless	
IP20	
IEC 61347-2-11 CISPR 15 IEC 62386-301 EMC-2004/108/EC LVD-2006/95/EC	

### **Dimensions**

Order code	Dimensions	Mounting centres
zc-sceneset-b6	W86 / H117 / D34 mm	106 / 60 mm
zc-sceneset-a6	W86 / H86 / D34 mm	60 mm

